

APPENDIX
SPACES TO BE INDICATED IN THE PLANS NEXT PAGE WITH NUMBERS
CORRESPONDING WITH THE TABLE BELOW

Class	Hold	In cargo hold	In cargo hold	On weather deck	On weather deck						
	No.1~No.3 (*1)	No.4 (*2), *6)	except above E./R (*3)	abover E/R							
1.1-1.6	X	X	P (*4)	X							
1.4S	P	P	P	P							
2.1	P (*7)	X	P	X							
2.2	P	P	P	X							
2.3 flammable	X	X	P	X							
2.3 non-flammable	X	X	P	X							
3 liquids FP<23°C	P	X	P	X							
3 liquids 23°C≤FP≤60°C	P	P	P	X							
4.1	P	P	P	X							
4.2	P	P	P	X							
4.3 liquids	P (*8)	P (*8)	P	X							
4.3 solids	P	P	P	X							
5.1	P	P	P	P (*5)							
5.2	X	X	P	X							
6.1 liquids	P	X	P	P							
6.1 liquids FP<23°C	P	X	P	X							
6.1 liquids 23°C≤FP≤60°C	P	X	P	X							
6.1 solids	P	P	P	P							
8 liquids	P	X	P	P							
8 liquids FP<23°C	P	X	P	X							
8 liquids 23°C≤FP≤60°C	P	P	P	X							
8 solids	P	P	P	P							
9	P	P (*9)	P	X							

P — Indicates PACKAGED GOODS PERMITTED
 A — Indicates PACKAGED AND BULK GOODS ALLOWED
 X — NOT ALLOWED
 Note: Cargoes in bulk may be listed individually by name and class



PLANS:

UNDER-DECK SPACES



ON DECK SPACES



Remarks related to the information in previous table:

- *1) For cargo hold No.1~No.3, explosion-proof type fans to be of IIB-T4 grade or equivalent. If any dangerous cargoes require explosion-proof grade higher than IIB-T4, such cargoes cannot be loaded(i.e. hydrogen, hydrogen mixture, ethyl nitrite, ethyl nitrate, etc.).
- *2) For cargo hold No.4, fans shall be of non-explosion-proof type.
- *3) Reefer containers on weather deck to be stowed 3m away from the mechanical ventilation outlet of dangerous cargo hold where dangerous cargo is loaded.
- *4) Dangerous goods of class 1.1 to 1.6 shall be stowed 3m horizontally away from the machinery space boundaries in all cases.
- *5) Except goods stowage away from sources of heat.
- *6) Dangerous goods shall be stowed in No.4 Cargo hold at least 3m away from the forward transverse bulkhead of engine room.
- *7) Hydrogen and hydrogen mixtures are not permitted.
- *8) Liquids flash point $<23^{\circ}$ C is not permitted.
- *9) Dangerous goods evolving flammable vapour is not permitted.

